ELSEVIER

Wear 189 (1995) 147

WEAR

Author Index of Volume 189

Atrens, A., 107

Belair, P., 70
Bi, J., 45
Blouet, J., 70

Cardou, A., 51
Chiou, Y.-C., 58
Cloutier, L., 51

De Castellar, M.D., 70
Doğan, O.N., 136
Du Mong, W., 32

Fiset, M., 51
Fox-Rabinovich, G.S., 25
Furuichi, H., 86

Goudreau, S., 51
Gras, R., 70

Hanau, T., 70
Hawk, J.A., 136
Hutchings, I.M., 66

Iyer, A., 100

Jacobs, P., 32

Klaffke, D., 117
Knothe, K., 91
Kovalev, A.I., 25
Kruth, J.P., 32

Lathabai, S., 122
Lee, R.-T., 58

Li, S., 45
Li, S.Z., 45
Li, Y., 20
Liang, Y.N., 45
Liebelt, S., 91

Ma, Z.Y., 45
Magham, H.G., 70
Matsuura, K., 86
Meozzi, M., 77
Meyer, U., 107

Pender, D.C., 122
Pujadas, J., 70

Rack, H.J., 1
Rajiv, E.P., 100
Romero, A., 70

Sang, K., 20
Sannino, A.P., 1
Seshadri, S.K., 100
Stevenson, A.N.J., 66
Su, G.Y., 45

Traveria, A., 70
Tura, J.M., 70

Van Der Biest, O., 32
Vanherck, P., 32
Vleugels, J., 32

Watanabe, S., 86

Yamazaki, K., 86
Yang, C.-R., 58

Zhou, Z.R., 51

Elsevier Science S.A.

ELSEVIER

Wear 189 (1995) 149–150

WEAR

Subject Index of Volume 189

Abrasion resistance
effect of carbide orientation on abrasion of high Cr white cast iron, 136
Adaptation
characteristic features of blanking die wear with consideration for the change in composition, structure and properties of contact surfaces, 25
Air blast
the influence of nozzle length on the divergence of the erodent particle stream in a gas-blast erosion rig, 66
Alumina
amorphous state formation and structural changes in α alumina by repeated rubbing, 86
Aluminium wire
effect of lubricant in electrical conductor fretting fatigue, 51
Amorphous state
amorphous state formation and structural changes in α alumina by repeated rubbing, 86

Bayer liquor
influence of environmental variables on erosion–corrosion of carbon steel in spent liquor reheaters in Bayer plant, 107
Blanking die
characteristic features of blanking die wear with consideration for the change in composition, structure and properties of contact surfaces, 25

Cavitation erosion
cavitation erosion of flame spray weld coating of nickel-base alloy powder, 20
Ceramics
microstructural influence in slurry erosion of ceramics, 122
Chemical wear
machining of steel with sialon ceramics: influence of ceramic and workpiece composition on tool wear, 32
Chromium carbides
effect of carbide orientation on abrasion of high Cr white cast iron, 136
Coating
cavitation erosion of flame spray weld coating of nickel-base alloy powder, 20
Coating composites
frictional properties and wear of a molybdenum coating and a bronze (Cu–10%Sn) with friction modifier fillers, 70
Composites
dry sliding wear of discontinuously reinforced aluminum composites: review and discussion, 1
wear behavior of reinforced aluminum alloys in various impact loadings, 45
tribological properties of cobalt–partially stabilized zirconia (PSZ) composites in dry sliding conditions, 100
Contact temperature
determination of temperatures for sliding contact with applications for wheel–rail systems, 91

Co–PSZ coatings
tribological properties of cobalt–partially stabilized zirconia (PSZ) composites in dry sliding conditions, 100
Corrosion
influence of environmental variables on erosion–corrosion of carbon steel in spent liquor reheaters in Bayer plant, 107

Disorder in a crystal
amorphous state formation and structural changes in α alumina by repeated rubbing, 86

EDX
frictional properties and wear of a molybdenum coating and a bronze (Cu–10%Sn) with friction modifier fillers, 70
Electrical conductor
effect of lubricant in electrical conductor fretting fatigue, 51
Electrodeposition
tribological properties of cobalt–partially stabilized zirconia (PSZ) composites in dry sliding conditions, 100
Equilibrium solubility
machining of steel with sialon ceramics: influence of ceramic and workpiece composition on tool wear, 32
Erosion
the influence of nozzle length on the divergence of the erodent particle stream in a gas-blast erosion rig, 66
influence of environmental variables on erosion–corrosion of carbon steel in spent liquor reheaters in Bayer plant, 107

Flash temperature
determination of temperatures for sliding contact with applications for wheel–rail systems, 91
Fretting cracking
effect of lubricant in electrical conductor fretting fatigue, 51
Fretting fatigue
effect of lubricant in electrical conductor fretting fatigue, 51
Friction
a simple coefficient for wear assessment, 77
amorphous state formation and structural changes in α alumina by repeated rubbing, 86
on the repeatability of friction and wear results and on the influence of humidity in oscillating sliding tests of steel–steel pairings, 117
Friction drive system
study on positioning accuracy of reciprocating friction drive system, 58

Gas blast
the influence of nozzle length on the divergence of the erodent particle stream in a gas-blast erosion rig, 66

Hardness
microstructural influence in slurry erosion of ceramics, 122

Elsevier Science S.A.

Humidity
on the repeatability of friction and wear results and on the influence of humidity in oscillating sliding tests of steel–steel pairings, 117

Impact abrasion
wear behavior of reinforced aluminum alloys in various impact loadings, 45
Impinging jet test rig
influence of environmental variables on erosion–corrosion of carbon steel in spent liquor reheaters in Bayer plant, 107
Interaction couples
machining of steel with sialon ceramics: influence of ceramic and workpiece composition on tool wear, 32

Lubricant
effect of lubricant in electrical conductor fretting fatigue, 51

Martensite transformation
determination of temperatures for sliding contact with applications for wheel–rail systems, 91
Microstructure
microstructural influence in slurry erosion of ceramics, 122

Nanocrystalline
amorphous state formation and structural changes in α alumina by repeated rubbing, 86
Nickel alloy
cavitation erosion of flame spray weld coating of nickel-base alloy powder, 20

Oscillating sliding
on the repeatability of friction and wear results and on the influence of humidity in oscillating sliding tests of steel–steel pairings, 117

Particulates
influence of environmental variables on erosion–corrosion of carbon steel in spent liquor reheaters in Bayer plant, 107
Positioning accuracy
study on positioning accuracy of reciprocating friction drive system, 58
Powder metallurgy
frictional properties and wear of a molybdenum coating and a bronze (Cu–10%Sn) with friction modifier fillers, 70

Reinforced aluminium
dry sliding wear of discontinuously reinforced aluminum composites: review and discussion, 1
Repeatability
on the repeatability of friction and wear results and on the influence of humidity in oscillating sliding tests of steel–steel pairings, 117
Rough surface
determination of temperatures for sliding contact with applications for wheel–rail systems, 91

Sand-blasting erosion
wear behavior of reinforced aluminum alloys in various impact loadings, 45
Secondary structures
characteristic features of blanking die wear with consideration for the change in composition, structure and properties of contact surfaces, 25
SEM
frictional properties and wear of a molybdenum coating and a bronze (Cu–10%Sn) with friction modifier fillers, 70
Severe wear
study on positioning accuracy of reciprocating friction drive system, 58
Sialon ceramics
machining of steel with sialon ceramics: influence of ceramic and workpiece composition on tool wear, 32
Sliding contact
determination of temperatures for sliding contact with applications for wheel–rail systems, 91
Sliding wear
dry sliding wear of discontinuously reinforced aluminum composites: review and discussion, 1
wear behavior of reinforced aluminum alloys in various impact loadings, 45
Slurry erosion
microstructural influence in slurry erosion of ceramics, 122
Steel
machining of steel with sialon ceramics: influence of ceramic and workpiece composition on tool wear, 32
Surface analysis
frictional properties and wear of a molybdenum coating and a bronze (Cu–10%Sn) with friction modifier fillers, 70

T-curve (R-curve) behavior
microstructural influence in slurry erosion of ceramics, 122
Test method
the influence of nozzle length on the divergence of the erodent particle stream in a gas-blast erosion rig, 66
Toughness
microstructural influence in slurry erosion of ceramics, 122
Transformation
amorphous state formation and structural changes in α alumina by repeated rubbing, 86
Tribological properties
tribological properties of cobalt–partially stabilized zirconia (PSZ) composites in dry sliding conditions, 100
Tribological system
a simple coefficient for wear assessment, 77
Tribology
a simple coefficient for wear assessment, 77
Two-phase flow
influence of environmental variables on erosion–corrosion of carbon steel in spent liquor reheaters in Bayer plant, 107

Wear
characteristic features of blanking die wear with consideration for the change in composition, structure and properties of contact surfaces, 25
a simple coefficient for wear assessment, 77
tribological properties of cobalt–partially stabilized zirconia (PSZ) composites in dry sliding conditions, 100
on the repeatability of friction and wear results and on the influence of humidity in oscillating sliding tests of steel–steel pairings, 117
Wear coefficient
a simple coefficient for wear assessment, 77
Wear resistance
dry sliding wear of discontinuously reinforced aluminum composites: review and discussion, 1
Wheel–rail system
determination of temperatures for sliding contact with applications for wheel–rail systems, 91
White cast iron
effect of carbide orientation on abrasion of high Cr white cast iron, 136

XPS
frictional properties and wear of a molybdenum coating and a bronze (Cu–10%Sn) with friction modifier fillers, 70